Click to prove you're human

If two or more waves collide, they are said to interfere. Interference is a property of waves. In this article, how interference occurs in different types of waves is explained.Figure 1: Interference of WavesA. InterferenceIf two or more waves overlap, the resultant displacement is the sum of the individual displacements. Displacement is a vector quantity. The overlapping waves are said to interfere. This occurrence is called as interference.Interference of two waves may lead to a resultant wave of either a larger or a smaller displacement than either of the two component waves. Interference can be demonstrated in a ripple tank by using two-point sources. A ripple tank used to study the interference of two waves is shown in Figure 2.Figure 2: Ripple TankInterference of two circular waves is shown in Figure 2. If two waves arrive in phase (their crests arrive at exactly the same time), they will interfere constructively. A resultant wave will be produced, which has crests much higher than the two individual waves, and troughs much deeper.If the two waves arrive in antiphase (with a phase difference of radians or 180), the peaks of one wave arrive at the same time as the troughs from the other, and they will interfere destructively. The resultant wave will have smaller amplitude. Figure 3 shows the interference pattern of two circular waves.This phase difference may be produced by allowing the two sets of waves to travel different distances this difference in distance of travel is called the path difference.Figure 3: Interference Pattern of Two Circular WavesB. Interference of Sound WavesInterference of sound waves is possible when two or more sound waves having the same frequency collide. The waves with the same frequency (constant phase difference between them) are called coherent waves.Consider sound waves from two loudspeakers connected to the same signal generator and amplifier, so that each speaker produces a note of the same frequency. Moving about in the space around the speakers, one can hear loud sound where sound waves interfere constructively. In places where the waves interfere destructively, the note is much quieter than elsewhere in the pattern.C. Interference of Light WavesThomas Young demonstrated how light waves could produce an interference pattern using an experiment. A monochromatic light source (a source of one colour, and hence one wavelength) is placed behind a single slit to create a small, well-defined source of light. Light from this source is diffracted at the slit (S0), producing two light sources at the double slit (S1 & S2). Because these two light sources originate from the same primary sources, they are coherent and create a sustained and observable interference pattern. The pattern observed on the screen is a series of bright and dark fringes. This experiment is called the Youngs double slit experiment. It is illustrated in Figure 4.Figure 4: Youngs Double Slit ExperimentThe distance on the screen between successive bright fringes is called the fringe width. The fringe width is related to the wavelength of the light source. It can be calculated by the following equation:Where, Wavelength of the light source (m).D Distance between screen and double slit (m).d Distance between centres of two slits S1 & S2 (m).D. SummaryThe overlapping waves are said to interfere. This occurrence is called as interference.If two waves arrive in phase (their crest arrive at exactly the same time), they will interfere constructively.If the two waves arrive in antiphase (with a phase difference of radians or 180), the peaks of one wave arrive at the same time as the troughs from the other, they will interfere destructively.Difference in distance travelled by two waves is called the path difference.Waves with the same frequency (constant phase difference between them) are called coherent waves.Monochromatic light consists of one colour, and hence one wavelength.Youngs double slit experiment is used to study the interference of light waves.In Youngs double slit experiment, the distance on the screen between successive bright fringes is called the fringe width. Fringe width can be calculated by the equation (D)/d. Interference of light is defined as: When two or more light waves having the same frequency, same wavelength and same amplitude meet together in a medium at a point, they cancel or enhance the effect of each other at that point. This phenomenon is called interference of light waves.There are two types of interference of light: Constructive interference Destructive interference What is Constructive interference? When two light waves superpose with each other in such a way that the crest of one wave falls on the crest of the second wave, and the trough of one wave falls on the trough of the second wave, then the resultant wave has larger amplitude and intensity. Such type of interference is called constructive interference. Some of its effects are: In constructive interference, two waves of light reinforce each other. In constructive interference, a bright fringe is obtained on the screen. What is Destructive Interference? In destructive interference When two light waves superpose with each other in such a way that the crest of one wave coincides with the trough of the second wave, then the amplitude and intensity of the resultant wave become zero. Some of its effects are: two waves cancel the effects of each other. Due to a dark fringe is obtained on the screen. Conditions for interference In order to observe the interference of light waves, the following conditions must be met. The two light sources must be coherent, that is, they must maintain a constant phase with respect to each other. The two light sources should be monochromatic, that is, of a single wavelength. The principle of superposition must apply. Now! Watch video about interference. Youngs Double-slit experiment The interference of light can be described by Youngs double-slit experiment. Youngs experiment provided the first conclusive proof of the wave nature of light. Consider plane waves incident on two slits separated by distance d as shown in the figure. The light waves from these two slits combine at a point P on the screen which is at a distance D from the two slits. Superposition of these waves produces a series of bright and dark fringes that are observed on the screen. If the waves arrive at the screen in such a way that at some points crests fall on crests and troughs fall on troughs then a bright fringe is seen on the screen due to constructive interference. There are some points on the screen where crests meet troughs then a dark fringe is seen on the screen. The bright fringe is called maxima and a dark fringe is called minima. Youngs experiment equation: Watch also video about young double slit experiment: Related topics in our websites are given below in the list: External sources wave_propagation) Whenever energy ripples through space, there is a wave. In fact, wave motion can be defined as a type of harmonic motion (repeated movement of a particle about a position of equilibrium, or balance) that carries energy from one place to another without actually moving any matter. A wave on the ocean is an example of a mechanical wave, or one that involves matter; but though the matter moves in place, it is only the energy in the wave that experiences net movement. Wave motion is related to oscillation, a type of harmonic motion in one or more dimensions. There is one critical difference, however: oscillation involves no net movement, only movement in place, whereas the harmonic motion of waves carries energy from one place to another. Yet, individual waves themselves are oscillating even as the overall wave pattern moves. A transverse wave forms a regular up-and-down pattern in which the oscillation is perpendicular to the direction the wave is moving. Ocean waves are transverse, though they also have properties of longitudinal waves. In a longitudinal wave, of which a sound wave is the best example, oscillation occurs in the same direction as the wave itself. Some waves, composed of pulses, do not follow regular patterns. However, the waves of principal concern in the present context are periodic waves, ones in which a uniform series of crests and troughs follow each other in regular succession. Periodic motion is movement repeated at regular intervals called periods. In the case of wave motion, a period (represented by the symbol T) is the amount of time required to complete one full cycle of the wave, from trough to crest and back to trough. Period can be mathematically related to several other aspects of wave motion, including wave speed, frequency, and wavelength. Frequency (abbreviated f) is the number of waves passing through a given point during the interval of one second. It is measured in Hertz (Hz), named after nineteenth-century German physicist Heinrich Rudolf Hertz (1857-1894), and a Hertz is equal to one cycle of oscillation per second. Higher frequencies are expressed in terms of kilohertz (kHz; 10 3 or 1,000 cycles per second) or megahertz (MHz; 10 6 or 1 million cycles per second.) Wavelength (represented by the symbol abbreviated , the Greek letter lambda) is the distance between a crest and the adjacent crest, or a A PIANO TUNER , USING A TUNING FORK SUCH AS THE ONES SHOWN ABOVE , UTILIZES INTERFERENCE TO TUNE THE INSTRUMENT . (Bettmann/Corbis . Reproduced by permission.) trough and an adjacent trough, of a wave. The higher the frequency, the shorter the wavelength. Another parameter for describing wave motionone that is mathematically independent from the quantities so far describedis amplitude, or the maximum displacement of particles from a position of stable equilibrium. For an ocean wave, amplitude is the distance from either the crest or the trough to the level that the ocean would maintain if it were perfectly still. Superposition and Interference The principle of superposition holds that when several individual but similar physical events occur in close proximity, the resulting effect is the sum of the magnitude of the separate events. This is akin to the popular expression, "The whole is greater than the sum of the parts," and it has numerous applications in physics. Where the strength of a gravitational field is being measured, for instance, superposition dictates that the strength of that field at any given point is the sum of the mass of the individual particles in that field. In the realm of electromagnetic force, the same statement applies, though the units being added are electrical charges or magnetic poles, rather than quantities of mass. Likewise, in an electrical circuit, the total current or voltage is the sum of the individual currents and voltages in that circuit. Superposition applies only in equations for linear eventsthat is, phenomena that involve movement along a straight line. Waves are linear phenomena, and, thus, the principle describes the behavior of all waves when they come into contact with one another. If two or more waves enter the same region of space at the same time, then, at any instant, the total disturbance produced by the waves at any point is equal to the sum of the disturbances produced by the individual waves. The principle of superposition does not require that waves actually combine; rather, the net effect is as though they were combined. The actual combination or joining of two or more waves at a given point in space is called interference, and, as a result, the waves produce a single wave whose properties are determined by the properties of the individual waves. If two waves of the same wavelength occupy the same space in such a way that their crests and I F THIS BOAT ' S WAKE WERE TO CROSS THE WAKE OF ANOTHER BOAT , THE RESULT WOULD BE BOTH CONSTRUCTIVE AND DESTRUCTIVE INTERFERENCE . (Photograph by Roger Ressmeyer/Corbis . Reproduced by permission.) troughs align, the wave they produce will have an amplitude greater than that possessed by either wave initially. This is known as constructive interference. The more closely the waves are in phasethat is, perfectly alignedthe more constructive the interference. It is also possible that two or more waves can come together such that the trough of one meets the crest of the other, or vice versa. In this case, what happens is destructive interference, and the resulting amplitude is the difference between the values for the individual waves. If the waves are perfectly unalignedin other words, if the trough of one exactly meets the crest of the othertheir amplitudes cancel out, and the result is no wave at all. It is easy to confuse interference with resonance, and, therefore, a word should be said about the latter phenomenon. The term resonance describes a situation in which force is applied to an oscillator at the point of maximum amplitude. In this way, the motion of the outside force is perfectly matched to that of the oscillator, making possible a transfer of energy. As with interference, resonance implies alignment between two physical entities; however, there are several important differences. Resonance can involve waves, as, for instance, when sound waves resonate with the vibrations of an oscillator, causing a transfer of energy that sometimes produces dramatic results. (See essay on Resonance.) But in these cases, a wave is interacting with an oscillator, not a wave with a wave, as in situations of interference. Furthermore, whereas resonance entails a transfer of energy, interference involves a combination of energy. The importance of this distinction is easy to see if one substitutes money for energy, and people for objects. If one passes on a sum of money to another person, a business, or an institutionas a loan, repayment of a loan, a purchase, or a giftthis is an example of a transfer. On the other hand, when married spouses each earn paychecks, their cash is combined. Transfer thus indicates that the original holder of the cash (or energy) no longer has it. Yet, if the holder of the cash combines funds with those of another, both share rights to an amount of money greater than the amount each originally owned. This is analogous to constructive interference. On the other hand, a husband and wife (or any other group of people who pool their cash) also share liabilities, and, thus, a married person may be subject to debt incurred by his or her spouse. If one spouse creates debt so great that the other spouse cannot earn enough to maintain the payments, this painful situation is analogous to destructive interference. In This Site, You Are Going To Learn about Science and its branches. This Site Includes lots of: Physics and its branches Chemistry Biology Mathematics Formulas, Theories, laws Lots more So If You Want To Get Great Results From this Website, Youll Love This Site. Lets Dive Right in What is Physics? Physics is the most fundamental branch of physical science which deals with the study of matter and energy, and their relationship with each other. Simple physics definition is, Physics is basically the study of how objects behave. Physics is an important and basic part of physical science. It is an experimental science. Classical Physics and Modern Physics are two Major Types of Physics. Types of Physics The Main Branches of Physics are: Classical Physics Quantum Physics or Modern Physics Classical Physics believes in a single nature, only the particle nature of matter. It provides the macroscopic vision of matter. It is based upon Newtons laws of mechanics and Maxwells laws of electromagnetism. Quantum Physics believes in the dual nature, both particle and wave nature of matter. It provides a microscopic vision of matter. It is based upon Plancks quantum theory of light and De Broglies idea of matter-wave. In the practical field, The common branches of Physics are: If you are confused about clicking on which type of topics then visit our site map in which all topics are listed on individuals branches of physics. Besides this, you can also use a search bar to find wanted topics. More Related Topics in Physics: Related Physics Links: Wave interference is the phenomenon that occurs when two waves meet while traveling along the same medium to form a resultant wave of greater, lower or the same amplitude. Interferenceusually refers to the interaction of waves which have constant phase difference and same or nearly same frequency. Interference effects can be observed with all types of waves, for example, radio waves, light waves, sound waves, surface water waves or matter waves. Types of wave interference When two waves meet while traveling along the same medium, either the amplitudes of both waves are added or the amplitudes of both waves are subtracted. Based on this, the wave interference is of two types: constructive interference and destructive interference. Constructive wave interference The wave interference is said to be a constructive wave interference if the crest of a wave meets the crest of another wave of the same frequency at the same point. or Constructivewave interference is a wave interference which occurs when in phase waves meets with each other and forms a new wave with greater amplitude. When two in phase waves having the same frequency meets at the same place at the same time, the amplitudes of the two waves are simply added together. The resultant wave amplitude is greater than that of the original wave. Consider two sound waves traveling in the same medium as shown in the below figure. The sound wave X amplitude is 1 unit and the sound wave Y amplitude is also 1 unit. When these two sound waves having the same frequency meets at the same time at the same place, the amplitudes of the two sound waves are added together. Therefore, the resultant sound wave (Z) amplitude is greater than that of the original wave. I.e. Z = X + Y = 1 + 1 = 2 units Theconstructive interference is pretty normal and natural. Example: Theconstructive wave interference occurs naturally. However, we can also create the constructive interference by using two speakers. If we place two speakers side-by-side, point them in the same direction, and play the same frequency, we get a constructive interference. As we know, sound means the vibrations that travel through the air. Both speaker 1 and speaker 2 pushes the air forwards. Hence, the vibrations travel in the forward direction (same direction) through the air. (Amplitudemeans the maximum extent of a vibration from the point of equilibrium.) If we stand in front of the two speakers, the vibrations produced by two speakers will be added up in the air. As a result, we hear a sound which is much louder than the individual speakers would produce. In other words, if we stand in front of the two speakers, the amplitudes of the two sound waves are added up. As a result, we hear a sound which is much louder than the individual speakers would produce. This is nothing but a constructive interference. Destructivewave interference The wave interference is said to be a destructive wave interference if the crest of a wave meets the trough of another wave of the same frequency. or Destructivewave interference is a wave interference which occurs when out of phase waves meets with each other and forms a new wave with lower amplitude or zero amplitude. Consider two sound waves traveling in the same medium that are out of phase as shown in the below figure. The sound wave X amplitude is 1 unit and the sound wave Y amplitude is also 1 unit. When these two sound waves having the same frequency meets each other, the amplitudes of the two sound waves cancels each other. Therefore, the resultant sound wave (Z) amplitude is zero or it is lower than that of the original wave. I.e. Z = X + Y = 1 + (- 1) = 0 units Example: As we know, if we place two speakers side-by-side, point them in the same direction, and play the same frequency, we get a constructive interference. Now imagine that we start moving one of the speakers backward, at some point, the two sound waves will become out of phase. So lets see what will happen if we stand in front of two speakers which are producing the out of phase sound waves. (Amplitudemeans the maximum extent of a vibration from the point of equilibrium.) If we stand in front of the two speakers, the speaker 1 one pushes the air in the forward direction and the speaker 2 pulls the air backwards. Hence, the vibrations produced by speaker 1 travels in the forward direction and the vibrations produced by speaker 2 travels in the backward direction. That means the two vibrations produced by speaker 1 and speaker 2 travels in the opposite directions. Hence, the two vibrations cancel out each other. As result, no vibration will reach your ear. We know that sound means vibrations traveling through the air. Therefore, you will not hear any sound. This is nothing but a destructive interference. How far back must we move the speaker to go from constructive to destructive interference? If the speakers are separated by half a wavelength, then there is a destructive interference. If the speakers are separated by one wavelength, then again there is a constructive interference. That means, for every half-wavelength separation, the constructive and destructive interferences changes alternatively. LearnPracticeImproveSucceedRegistered Students7.1+ CroreStudent Selections4+ Lacs Tests Attempted242+ CroreClasses Attended5.5+ CroreGet unlimited access to the most relevant Mock Tests, on India's Structured Online Test series platformWhat you get with Testbook PassExplore Testbook Pass RRB NTPC Mock Test Series 2024-25 (CBT 1 + CBT 2) 1792 Total Tests | 16 Free Tests English,Hindi + 6 MoreAvailable in: English, Hindi, Bengali, Marathi, Telugu, Tamil, Gujarati, Kannada, 1 Ultimate Live Test191 Most Saved Qs CT78 +1522 more tests SSC CGL (Tier I & Tier II) Mock Test 2025 (New) 1088 Total Tests | 3 Free Tests1 Ultimate Live Test120 2024 PYQ233 Chapter Test (Tier I)+734 more tests RRB Junior Hindi Translator 2025 Mock Test Series 246 Total Tests | 4 Free Tests English,Hindi + 7 MoreAvailable in: English, Hindi, Bengali, Marathi, Telugu, Tamil, Gujarati, Kannada, Oria, 2 Free Test193 Chapter Test13 Current Affairs+38 more tests RRB Group D Mock Test Series 2024-25 932 Total Tests | 4 Free Tests English,Hindi + 7 MoreAvailable in: English, Hindi, Bengali, Marathi, Telugu, Tamil, Gujarati, Kannada, Oria, 1 Ultimate Live Test159 Latest TCS Exam 202426 General Science Special+746 more testsExplore all Test Series With 1.8+ Crore Students and One of the best Selection rate in India amongst online learning platforms, you can surely rely on us to excel.Get Started For FreeLearn from the masters of the subject, in the most engaging yet simplified waysGet a detailed breakdown of your strengths & weaknesses and discover insights to improve your scoreFeel the thrill of a real exam. Improve your time & pressure management skillsLearn in the language you are most comfortable with. Choose from any of our 8 languagesAIR 1|Delhi Judicial 2024Start your learning journey now!LearnPracticeImproveSucceedA mechanical type of wave, which observes displacement in the same direction as the magnitude of the wave is referred to as Longitudinal Waves. There are multiple types of longitudinal waves, for example, Ultrasonic waves, Sound Waves, Seismic P Waves, etc. And this topic plays an important role in explaining how various important quantities such as displacement, amplitude, frequency, etc, change along or vary with the Longitudinal waves, which we are going to explain in much more detail below.From the above diagram, you can understand the different types of quantities present in the Longitudinal Wave. Moreover, the distance between the two compressions and rarefaction in the diagram can be found by using wavelength. Based on Whether the two waves coincide with each other or not, there are further divided into two types, such as constructive interference and distractive interference.Constructive InterferenceWhen both compressions and rarefaction coincide with each other on the longitudinal wave, then it is called constructive interference.Destructive InterferenceAs you can guess, in this form of a longitudinal wave, the compression region, and the rarefaction region do not coincide with each other like constructive interference. Then it is referred to as destructive interference.Difference Between Longitudinal Waves and Transversal WavesNow that we have talked about the Longitudinal Waves. Let us discuss how both parts of longitudinal waves and transversal waves differ from each other. These differences are,ParametersLongitudinal WavesTransversal WavesDefinitionA wave moves in the direction of its displacement.A wave that moves perpendicular to its displacement.DimensionOne Dimensional WaveTwo-Dimensional WaveMediumIt can be observed in any type of medium, like Air, Gas, and Solid.Whereas Transverse waves can be found only in Gas and Liquid Medium.ConstituentsIt consists of compressions and refractions.It consists of troughs and crests.ExamplesSound Wave, and Ultrasonic WavesEarthquake S WaveFormula of Longitudinal WavesThe Longitudinal wave is mathematically expressed as,\(y(x,t)= y_{0}cos[\omega (t- \frac{x}{c})]\)Where y = displacement of a point in Longitudinal wave.X = distance traveled by the pointC = speed of a wave\(\omega \)=angular frequency of the waveT = time elapsed\(y_{0} \)= amplitude of oscillations\(\frac{x}{c} \) =TimeCharacteristics of Longitudinal WavesThere are many characteristics involved in Longitudinal Waves, which we will explain briefly here in this section.Rarefaction In a longitudinal wave, when the particles are furthest apart from each other, then they are called refraction.Amplitude The distance between the equilibrium position in the medium, and the rarefaction or compression is called amplitude.Frequency The number of wavelengths per second in the Longitudinal wave is referred to as frequency.Compression In a longitudinal wave, when the particles are much closer to each other than it is referred to as compression.Wavelength The distance between two consecutive points involving either compression or rarefactions is stated as wavelength.Period The time taken by the wave to cover one wavelength is described as a period.ConclusionThe above article provided a comprehensive description of Longitudinal Waves, Equations, Definitions as well as Characteristics. So, if you are struggling with any other topics or chapters in this particular subject, then it would be a better idea for you to join any good online coaching class. One such customized online interactive class is offered by the Tutoroot platform, which comes with various benefits including cost-effective prices, expert staff guidance, access to the best subject-related materials, and a lot more.AnswerVerifiedHint: Interferences are formed from the resultant of two different waveforms in which the displacements from the two waveforms are either reinforced or cancelled. So, we will first understand which type of waves produce interferences. Then we will define the mechanical wave and its types which will tell us about their orientation of interference formation which will give us the required information.Complete step by step answer:When two different waves while travelling along the same medium meet each other, a resultant wave is formed due to either the reinforcement or cancellation of the displacements of the two waveforms. As a result of both of these waves the medium takes a different shape due to their net effect on the particles in that medium. Interferences can be produced by any types of waves like light, acoustics, gravity, matter, etc.At a location, where the displacement of the two waves are in the same direction, constructive interference occurs and when they are opposite to each other, destructive interference occurs.Mechanical waves are formed due to the oscillation of matter which results in transfer of energy along a medium which helps the wave to propagate over large distances. These are of generally two types; Transverse wave and longitudinal wave.In longitudinal waves, the medium vibrates parallel to the wave direction and the interference formed by them is horizontal.While in transverse waves, the particles of the medium vibrate in a direction perpendicular to the direction of wave propagation and thus the interferences produced by them is verticalHence, option d is the correct answer.Note:All types of waves when passes through a narrow slit, get diffracted after coming in contact with the slit edges irrespective of the orientation of the wave. This diffraction of waves takes place which causes the formation of interferences. Share copy and redistribute the material in any medium or format for any purpose, even commercially. Adapt remix, transform, and build upon the material for any purpose, even commercially. The licensor cannot revoke these freedoms as long as you follow the license terms. Attribution You must give appropriate credit , provide a link to the license, and indicate if changes were made . You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use. ShareAlike If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original. No additional restrictions You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits. You do not have to comply with the license for elements of the material in the public domain or where your use is permitted by an applicable exception or limitation . No warranties are given. The license may not give you all of the permissions necessary for your intended use. For example, other rights such as publicity, privacy, or moral rights may limit how you use the material. Option 3 : In both types of waves CONCEPT: Interference is a process in which two waves superimpose on each other to form a new wave of greater or smaller amplitude. EXPLANATION: As we know that longitudinal waves are the waves in which particles are traveled the same direction or the opposite direction of, the direction of propagation of the wave. Similarly, transverse waves are the waves in which particles are displaced perpendicular, to the direction of propagation of the wave. Interference event is observed in both types of waves i.e transverse waves as well as longitudinal waves because both waves can superimpose on each other. Indias #1 Learning Platform Start Complete Exam Preparation Daily Live MasterClasses Practice Question Bank Mock Tests & Quizzes Trusted by 7.1 Crore+ Students IntroductionTo understand the concept of interference, lets refresh our understanding of waves. Waves are disturbances that carry energy through a medium or space. They can be categorized into two main types: transverse waves and longitudinal waves. Transverse waves like ripples on a water surface, move perpendicular to the direction of the wave. Longitudinal waves, on the other hand, move parallel to the direction of the wave e.g. sound waves. Interference occurs when two or more waves meet or overlap. In this article, we will explore the concept of interference, types of interference, and standing waves.InterferenceWe all know the fact that all matter has volume. The reason is that objects cannot occupy the same space at the same time. Because waves carry energy but not matter, more than one wave can exist in the same place simultaneously. Two waves can meet, share the same space, and pass through each other without obstruction. When two or more waves share the same space, they interact with each other. This phenomenon is known as interference. Types of InterferenceThe result of interference can be constructive or destructive depending on how the waves interact.Constructive InterferenceConstructive interference occurs when the crests of one wave align with the crests of other waves, while their troughs also overlap. An example of constructive interference is shown in the mentioned figure. When waves combine in such a manner, a new wave is formed with higher crests and deeper troughs than the original wave. In simpler terms, the resulting wave has a larger amplitude than the original waves had.Destructive InterferenceDestructive interference arises when the crests of one wave coincide with the troughs of another wave. Consequently, the resulting wave exhibits a reduced amplitude compared to the original waves.Standing WavesRecalling the previous experiment, take a piece of rope and tie one end of the rope to the fixed point. Now, move the other end up in and downward direction, and the waves arise travel down the rope, and reflected back. When the rope is moved at specific frequencies, the rope appears to vibrate in loops. The loops arise in the rope due to the interference between the wave created and the reflected wave. The resulting wave is known as a standing wave.A standing wave is characterized by a stationary pattern, in which portions of the wave are at the rest position due to total destructive interference and other segments have a large amplitude due to constructive interference.It is important to note that although the wave may appear motionless, in reality, the waves are traveling in both directions. Standing waves can manifest in various types of waves, including transverse waves as shown here, as well as longitudinal waves.Resonant FrequencyStanding waves can be created at more than one frequency. The frequencies at which standing waves occurred are called resonant frequencies. Resonance takes place when an object vibrating at or close to the resonant frequency of another object, induces vibrations in the second object. As a result, the resonating object absorbs energy from the vibrating object and in turn, begins to vibrate as well.The Tacoma Narrows BridgeThe phenomenon of resonance played a significant role in the unfortunate demise of the Tacoma Narrows Bridge located in Washington. After its opening in July 1940, the bridge acquired the nickname "Galloping Gertie" due to its noticeable wavelike oscillations.These oscillations were primarily induced by wind passing over the bridge's structure. The wind caused vibrations that were close to the resonant frequency of the bridge. The wind's vibrations closely matched the resonant frequency of the bridge. Because the bridge was in resonance, it absorbed a substantial amount of energy from the wind and exhibited significant vibrations with a large amplitude.On November 7, 1940, a supporting cable slipped, leading to the initiation of twisting motions in the bridge. The combination of twisting and strong winds further amplified the bridge's amplitude of motion. Within a matter of hours, the amplitude grew to such an extent that the bridge eventually collapsed. Fortunately, all the people on the bridge at that time managed to escape before it collapsed into the river below.SummaryWhen two or more waves interact with each other, they overlap. This phenomenon is known as interference.Constructive interference occurs when two waves overlap in such a way that they generate a wave with a larger amplitude.Destructive interference occurs when two waves overlap in such a manner that they cancel out each other.A standing wave refers to a stationary pattern that emerges from the superposition of two or more waves traveling in opposite directions along the same line. Phenomenon resulting from the superposition of two wavesFor interference in radio communications, see Interference (communication)."Interference pattern" redirects here. For Moir patterns, see Moir pattern. For the medical term, see Interference pattern (electromyography).This article may be too technical for most readers to understand. Please help improve it to make it understandable to non-experts, without removing the technical details. (February 2022) (Learn how and when to remove this message)The interference of two waves. In phase: the two lower waves combine (left panel), resulting in a wave of added amplitude (constructive interference). Out of phase: (here by 180 degrees), the two lower waves combine (right panel), resulting in a wave of zero amplitude (destructive interference).Interfering water waves on the surface of a lakeIn physics, interference is a phenomenon in which two coherent waves are combined by adding their intensities or displacements with due consideration for their phase difference. The resultant wave may have greater amplitude (constructive interference) or lower amplitude (destructive interference) if the two waves are in phase or out of phase, respectively.Interference effects can be observed with all types of waves, for example, light, radio, acoustic, surface water waves, gravity waves, or matter waves as well as in loudspeakers as electrical waves.The word interference is derived from the Latin words inter which means "between" and fere which means "hit or strike", and was used in the context of wave superposition by Thomas Young in 1801.[1][2][3]Interference of right traveling (green) and left traveling (blue) waves in Two-dimensional space, resulting in final (red) waveInterference of waves from two point sourcesCropped tomography scan animation of laser light interference passing through two pinholes (side edges)The principle of superposition of waves states that when two or more propagating waves of the same type are incident on the same point, the resultant amplitude at that point is equal to the vector sum of the amplitudes of the individual waves.[4] If a crest of a wave meets a crest of another wave of the same frequency at the same point, then the amplitude is the sum of the individual amplitudesthis is constructive interference. If a crest of one wave meets a trough of another wave, then the amplitude is equal to the difference in the individual amplitudesthis is known as destructive interference. In ideal mediums (water, air are almost ideal) energy is always conserved, at points of destructive interference, the wave amplitudes cancel each other out, and the energy is redistributed to other areas. For example, when two pebbles are dropped in a pond, a pattern is observable; but eventually waves continue, and only when they reach the shore is the energy absorbed away from the medium.Photograph of 1.5cm x 1cm region of soap film under white light. Varying film thickness and viewing geometry determine which colours undergo constructive or destructive interference. Small bubbles significantly affect surrounding film thickness.Constructive interference occurs when the phase difference between the waves is an even multiple of (180), whereas destructive interference occurs when the difference is an odd multiple of . If the difference between the phases is intermediate between these two extremes, then the magnitude of the displacement of the summed waves lies between the minimum and maximum values.Consider, for example, what happens when two identical stones are dropped into a still pool of water at different locations. Each stone generates a circular wave propagating outwards from the point where the stone was dropped. When the two waves overlap, the net displacement at a particular point is the sum of the displacements of the individual waves. At some points, these will be in phase, and will produce a maximum displacement. In other places, the waves will be in anti-phase, and there will be no net displacement at these points. Thus, parts of the surface will be stationarythese are seen in the figure above and to the right as stationary blue-green lines radiating from the centre.Interference of light is a unique phenomenon in that we can never observe superposition of the EM field directly as we can, for example, in water. Superposition in the EM field is an assumed phenomenon and necessary to explain how two light beams pass through each other and continue on their respective paths. Prime examples of light interference are the famous double-slit experiment, laser speckle, anti-reflective coatings and interferometers. In addition to classical wave model for understanding optical interference, quantum matter waves also demonstrate interference. The above can be demonstrated in one dimension by deriving the formula for the sum of two waves. The equation for the amplitude of a sinusoidal wave traveling to the right along the x-axis is W 1 (x , t) = A cos (k x t) {\displaystyle W_{1}(x,t)=A\cos(kx-\omega t)} where A {\displaystyle A} is the peak amplitude, k = 2 / {\displaystyle k=2\pi /\lambda } is the wavenumber and = 2 f {\displaystyle \omega =2\pi f} is the angular frequency of the wave. Suppose a second wave of the same frequency and amplitude but with a different phase is also traveling to the right W 2 (x , t) = A cos (k x t +) {\displaystyle W_{2}(x,t)=A\cos(kx-\omega t+\varphi)} where {\displaystyle \varphi } is the phase difference between the waves in radians. The two waves will superpose and add: the sum of the two waves is W 1 + W 2 = A [cos (k x t) + cos (k x t +)] . {\displaystyle W_{1}+W_{2}=A[\cos(kx-\omega t)+\cos(kx-\omega t+\varphi)].} Using the trigonometric identity for the sum of two cosines: cos a + cos b = 2 cos (a b 2) cos (a + b 2) , {\textstyle \cos a+\cos b=2\cos \left({a-b \over 2}\right)\cos \left({a+b \over 2}\right),} this can be written W 1 + W 2 = 2 A cos (2) cos (k x t + 2) . {\displaystyle W_{1}+W_{2}=2A\cos \left({\varphi \over 2}\right)\cos \left(kx-\omega t+{\varphi \over 2}\right).} This represents a wave at the original frequency, traveling to the right like its components, whose amplitude is proportional to the cosine of / 2 {\displaystyle \varphi /2} .Constructive interference: If the phase difference is an even multiple of : = , 4 , 2 , 0 , 2 , 4 , {\displaystyle \varphi =\ldots ,-4\pi ,-2\pi ,0,2\pi ,4\pi ,\ldots } then | cos (/ 2) | = 1 {\displaystyle \left|\cos(\varphi /2)\right|=1} , so the sum of the two waves is a wave with twice the amplitude W 1 + W 2 = 2 A cos (k x t) {\displaystyle W_{1}+W_{2}=2A\cos(kx-\omega t)} Destructive interference: If the phase difference is an odd multiple of : = , 3 , , , 3 , 5 , {\displaystyle \varphi =\ldots ,-3\pi ,\,-\pi ,\,\pi ,\,3\pi ,\,5\pi ,\ldots } then cos (/ 2) = 0 {\displaystyle \cos(\varphi /2)=0\,} , so the sum of the two waves is zero W 1 + W 2 = 0 {\displaystyle W_{1}+W_{2}=0} Geometrical arrangement for two plane wave interference Interference fringes in overlapping plane wavesA simple form of interference pattern is obtained if two plane waves of the same frequency intersect at an angle.One wave is travelling horizontally, and the other is travelling downwards at an angle to the first wave. Assuming that the two waves are in phase at the point B, then the relative phase changes along the x-axis. The phase difference at the point A is given by = 2 d = 2 x sin . {\displaystyle \Delta \varphi ={\frac {2\pi d}{\lambda }}={\frac {2\pi x\sin \theta }{\lambda }}.} It can be seen that the two waves are in phase when x sin = 0 , 1 , 2 , , {\displaystyle {\frac {x\sin \theta }{\lambda }}=0,\pm 1,\pm 2,\ldots ,} and are half a cycle out of phase when x sin = 1 2 , 3 2 , {\displaystyle {\frac {x\sin \theta }{\lambda }}=\pm {\frac {1}{2}},\pm {\frac {3}{2}},\ldots } Constructive interference occurs when the waves are in phase, and destructive interference when they are half a cycle out of phase. Thus, an interference fringe pattern is produced, where the separation of the maxima is d f = sin {\displaystyle d_{f}= {\frac {\lambda }{\sin \theta }}} and df is known as the fringe spacing. The fringe spacing increases with increase in wavelength, and with decreasing angle .The fringes are observed wherever the two waves overlap and the fringe spacing is uniform throughout.Optical interference between two point sources that have different wavelengths and separations of sources.A point source produces a spherical wave. If the light from two point sources overlaps, the interference pattern maps out the way in which the phase difference between the two waves varies in space. This depends on the wavelength and on the separation of the point sources. The figure to the right shows interference between two spherical waves. The wavelength increases from top to bottom, and the distance between the sources increases from left to right.When the plane of observation is far enough away, the fringe pattern will be a series of almost straight lines, since the waves will then be almost planar.Interference occurs when several waves are added together provided that the phase differences between them remain constant over the observation time.It is sometimes desirable for several waves of the same frequency and amplitude to sum to zero (that is, interfere destructively, cancel). This is the principle behind, for example, 3-phase power and the diffraction grating. In both of these cases, the result is achieved by uniform spacing of the phases.It is easy to see that a set of waves will cancel if they have the same amplitude and their phases are spaced equally in angle. Using phasors, each wave can be represented as A e i n {\displaystyle Ae^{i\varphi _{n}}} for N {\displaystyle N} waves from n = 0 {\displaystyle n=0} to n = N 1 {\displaystyle n=N-1} , where n n 1 = 2 N . {\displaystyle \varphi _{n}-\varphi _{n-1}={\frac {2\pi }{N}}.} To show that n = 0 N 1 A e i n = 0 {\displaystyle \sum _{n=0}^{N-1}Ae^{i\varphi _{n}}=0} one merely assumes the converse, then multiplies both sides by e i 2 N . {\displaystyle e^{i{\frac {2\pi }{N}}}.} The FabryProt interferometer uses interference between multiple reflections.A diffraction grating can be considered to be a multiple-beam interferometer; since the peaks which it produces are generated by interference between the light transmitted by each of the elements in the grating; see interference vs. diffraction for further discussion.Mechanical and gravity waves can be directly observed: they are real-valued wave functions; optical and matter waves cannot be directly observed: they are complex valued wave functions. Some of the differences between real valued and complex valued wave interference include:The interference involves different types of mathematical functions: A classical wave is a real function representing the displacement from an equilibrium position; an optical or quantum wavefunction is a complex function. A classical wave at any point can be positive or negative; the quantum probability function is non-negative.Any two different real waves in the same medium interfere; complex waves must be coherent to interfere. In practice this means the wave must come from the same source and have similar frequenciesReal wave interference is obtained simply by adding the displacements from equilibrium (or amplitudes) of the two waves; In complex wave interference, we measure the modulus of the wavefunction squared.Creation of interference fringes by an optical flat on a reflective surface. Light rays from a monochromatic source pass through the glass and reflect off both the bottom surface of the flat and the supporting surface. The tiny gap between the surfaces means the two reflected rays have different path lengths. In addition the ray reflected from the bottom plate undergoes a 180 phase reversal. As a result, at locations (a) where the path difference is an odd multiple of /2, the waves reinforce. At locations (b) where the path difference is an even multiple of /2 the waves cancel. Since the gap between the surfaces varies slightly in width at different points, a series of alternating bright and dark bands, interference fringes, are seen.Because the frequency of light waves (~1014 Hz) is too high for currently available detectors to detect the variation of the electric field of the light, it is possible to observe only the intensity of an optical interference pattern. The intensity of the light at a given point is proportional to the square of the average amplitude of the wave. This can be expressed mathematically as follows. The displacement of the two waves at a point r is: U 1 (r , t) = A 1 (r) e i [1 (r) t] {\displaystyle U_{1}(\mathbf {r} ,t)=A_{1}(\mathbf {r})e^{i[\varphi _{1}(\mathbf {r})-\omega t]}} U 2 (r , t) = A 2 (r) e i [2 (r) t] {\displaystyle U_{2}(\mathbf {r} ,t)=A_{2}(\mathbf {r})e^{i[\varphi _{2}(\mathbf {r})-\omega t]}} where A represents the magnitude of the displacement, represents the phase and represents the angular frequency.The displacement of the summed waves is U (r , t) = A 1 (r) e i [1 (r) t] + A 2 (r) e i [2 (r) t] . {\displaystyle U(\mathbf {r} ,t)=A_{1}(\mathbf {r})e^{i[\varphi _{1}(\mathbf {r})-\omega t]}+A_{2}(\m